

# PRODUCT DATASHEET

## SMART+ Wifi Planon 600x100mm TW

SMART+ Planon Frameless TW | Frameless panel luminaires with WiFi technology



---

### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

---

### Product benefits

- Easy and quick installation

---

### Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Dimmable
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Network protocol: WiFi



## TECHNICAL DATA

### Electrical data

|                                                             |               |
|-------------------------------------------------------------|---------------|
| Nominal wattage                                             | 28.00 W       |
| Nominal voltage                                             | 220...240 V   |
| Mains frequency                                             | 50...60 Hz    |
| Nominal current                                             | 137.500 mA    |
| Max. number of luminaires per miniature circuit breaker B16 | 16            |
| Max. number of luminaires per miniature circuit breaker C16 | 24            |
| Power factor $\lambda$                                      | > 0.90        |
| Total harmonic distortion                                   | < 20 %        |
| Protection class                                            | II            |
| Operating mode                                              | Mains voltage |


### Photometrical data

|                                                              |                      |
|--------------------------------------------------------------|----------------------|
| Luminous flux                                                | 1800 lm              |
| Total luminous flux of contained light sources               | 3100 lm              |
| Luminous efficacy                                            | 64 lm/W              |
| Color temperature                                            | 3000...6500 K        |
| Reference control setting of contained light source (Kelvin) | 3000 K <sup>1)</sup> |
| Light color (designation)                                    | Tunable White        |
| Color rendering index Ra                                     | > 80                 |
| Standard deviation of color matching                         | < 6 sdcm             |
| Flickering metric (Pst LM)                                   | ≤1                   |
| Stroboscope effect metric (SVM)                              | ≤0.4                 |
| Photobiological safety group acc. to EN62778                 | RG0                  |
| Photobiological safety group acc. to EN62471                 | RG0                  |
| Beam angle                                                   | 110 °                |

1) Performing a reset will restore the default values set by the manufacturer

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 600.00 mm |
| Width          | 100.00 mm |
| Height         | 65.00 mm  |
| Product weight | 1420.00 g |



SMART WIFI PLANON  
FRAMELESS 60x10TW

Materials & Colors

|                                            |                               |
|--------------------------------------------|-------------------------------|
| Product color                              | White                         |
| Housing color                              | White                         |
| Body material                              | Aluminum                      |
| Cover material                             | Polymethylmethacrylate (PMMA) |
| Light emitting surface material            | PMMA                          |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C                        |
| Mercury content                            | 0.0 mg                        |

Application & Mounting

|                           |                         |
|---------------------------|-------------------------|
| Ambient temperature range | -20...+40 °C            |
| Type of connection        | Terminal, 2-Pole (L, N) |
| Type of protection        | IP20                    |
| Dimmable                  | Yes                     |
| Type of dimming           | WiFi                    |
| Mounting type             | Surface                 |
| Mounting location         | Ceiling                 |
| Application environment   | Indoor                  |
| With light source         | No                      |

Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 25000 h |
| Number of switching cycles | 15000   |

Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / EAC / UKCA |
| Luminaire with limited surface temperature, "D sign" | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

Additional product data

## Product remark

Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.

## EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

## DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                           |
|------------------------------------------------------------------------------------|----------------------------------------|-----------------------------------------|
|   | User instruction / safety instructions | SMART+ PLANON FRAMELESS                 |
|  | Declarations of conformity             | SMART WIFI PLANON FRAMELESS 60X10TWLEDV |
|  | Declarations of conformity UKCA        | SMART WIFI AND SUNATHOME                |
|  | EU Data Act                            | SMART WiFi Lamps and Luminaires         |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075484610 | Folding box<br>1             | 88 mm x 623 mm x 128 mm              | 1581.00 g    | 7.02 dm <sup>3</sup>  |
| 4058075484627 | Shipping box<br>6            | 662 mm x 307 mm x 310 mm             | 10645.00 g   | 63.00 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- Further information and frequently asked questions (FAQs) at [www.ledvance.com/consumer/smart/faq](http://www.ledvance.com/consumer/smart/faq)

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.