

# PRODUCT DATASHEET

## SP HOLDER DN68 H65

SPOT HOLDER | Spacer to increase distance between spotlight and thermal insulation material



### Areas of application

- Ceilings in low energy houses
- Ceilings with thermal insulation material

### Product benefits

- Increase distance between spotlight and thermal insulation material
- Protects moisture barrier foil from hot surface of spotlight and driver
- Robust: 4-leg spacer to hold thermal insulation material
- Improved lifetime for LED and driver thanks to increased air-volume

### Product features


- Material: fibre-reinforced polyamide PA66
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- Suitable only for LEDVANCE SPOTs in 68 mm cut-out



## TECHNICAL DATA

### Dimensions & Weight

|                |         |
|----------------|---------|
| Length         | 93.0 mm |
| Width          | 93.0 mm |
| Height         | 73 mm   |
| Product weight | 19.00 g |



SP HOLDER DN68 H65

### Materials & Colors

|               |               |
|---------------|---------------|
| Product color | Grey          |
| Body material | Polyamid (PA) |

### Application & Mounting

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Mounting type             | Recessed     |
| Mounting location         | Ceiling      |
| Mounting diameter         | 68...83 mm   |
| Mounting depth            | 65,0 mm      |
| Replaceable light source  | No           |






### Certificates & Standards

|           |                      |
|-----------|----------------------|
| Standards | CE / CB / UKCA / EAC |
|-----------|----------------------|

### Safety advice

- This spacer is only allowed to be used in combination with SP AIR FIX or SP AIR ADJ!

## DOWNLOAD DATA

| Documents and certificates   |  | Document name                                      |
|--|--|--|
|  | User instruction / safety instructions | UI SP AIR FIX P                                    |
|  | Declarations of conformity             | CE Declaration of Conformity SPOTLIGHT ACCESSORY   |
|  | Declarations of conformity UKCA        | UKCA Declaration of Conformity SPOTLIGHT ACCESSORY |
|  | Declarations of conformity UKCA        | SP ACC   |
| Tender texts   |  | Document name                                      |
|  | Tender documents                       | SPOT HOLDER DN68 H65-EN                            |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854013478 | BAG<br>1                     | 95 mm x 95 mm x 73 mm                | 23.00 g      | 0.66 dm <sup>3</sup>  |
| 4099854013485 | Shipping box<br>20           | 175 mm x 175 mm x 135 mm             | 522.00 g     | 4.13 dm <sup>3</sup>  |
| 4099854013492 | Shipping box<br>360          | 550 mm x 545 mm x 300 mm             | 2291.00 g    | 89.93 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.