

# PRODUCT DATASHEET TRUSYS FLEX P RAIL 600 8P END WT

# TruSys® FLEX ENERGY RAIL 8-POLE | 8-pole mounting rail

#### Areas of application

- Industry halls, high rack warehouse, hardware stores



- Simple installation

**Product benefits** 

- High flexibility thanks to three available lengths (1500 mm, 3000 mm, 4500 mm and 1500 mm end rail)
- Version of 600 mm rail to be used with TRUSYS FLEX SENSOR TRACK

#### **Product features**

- Through wired with 8 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors




#### **TECHNICAL DATA**

### Electrical data

Protection class	

# **Dimensions & Weight**

Length	600 mm
Width	70.2 mm
Height	38.8 mm
Product weight	580.00 g



#### TRUSYS FLEX P RAIL 600 8P END WT

#### Materials & Colors

Product color	White
Body material	Steel

# Application & Mounting

Mounting location	Ceiling
With light source	No
Replaceable light source	No

#### Certificates & Standards

Standards	CE / CB / UKCA / ENEC / EAC

# EQUIPMENT / ACCESSORIES

- Various accessories available

#### DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
POF	Declarations of conformity	TRUSYS FLEX RAIL ST COVER	
PDF	Declarations of conformity UKC	A TRUSYS FLEX RAIL ST COVER	
	Tender texts	Document name	
	Tender documents	TruSys FLEX ENERGY RAIL 8 POLE 600 8P END WT-EN	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854193545	Sleeve 1	150 mm x 233 mm	597.00 g	
4099854193552	Shipping box 4	672 mm x 193 mm x 145 mm	2930.00 g	18.81 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.