# PRODUCT DATASHEET LED PAR30 75 36° DIM P 10W 927 E27

LED PAR30 DIM P | Dimmable LED reflector lamps PAR30 with retrofit screw base



#### Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Stepless dimming
- Very high dimmer compatibility, see also www.ledvance.com/dim
- Instant 100 % light, no warm-up time
- Lower energy consumption than incandescent or halogen lamps

#### **Product features**

- LED alternative to high voltage halogen lamps
- High color consistency: ≤ 6 SDCM
- Dimmable
- Base: E27
- Lamp made of glass





- Very high color rendering CRI > 90
- Lifetime up to 25,000 h


# TECHNICAL DATA

# Electrical data

Nominal wattage	10 W
Construction wattage	10.00 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	75 W
Nominal current	55 mA
Type of current	AC
Inrush current	0.23 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	145
Max. lamp number on MCB B16 A	232
Total harmonic distortion	≤ 130 %
Power factor $\lambda$	≥ 0.40

# Photometrical data

Luminous intensity	1400 cd
Luminous flux	633 lm
Nominal useful luminous flux 90°	633 lm
Luminous efficacy	63 lm/W
Lumen main.fact.at end of nom.life time	0.96
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	90
Light color	927
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	1400 cd
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4
-	



Everlight 67-23ST HKE 2700K

# Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	93.00 mm
Diameter	95.00 mm
Maximum diameter	95 mm
Product weight	140.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	72.9 °C

# Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.96

# Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes

Design / version	Spot
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

# Capabilities

Dimmable	Yes <sup>1)</sup>
----------	-------------------

<sup>1)</sup> Check dimmer compatibility at ledvance.com/compatibility

## Certificates & Standards

Energy efficiency class	G <sup>1)</sup>
Energy consumption	10.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG1

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Country-specific categorizations

Order reference LED PAR307536 D
---------------------------------

# LOGISTICAL DATA

Temperature range at storage	-20+80 °C

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	DLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Claim of equivalent power	Yes

Length	93.00 mm
Height	95.00 mm
Width	95.00 mm
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	NARROW_CONE_90
Survival factor	0.90
Displacement factor	20.5
LED light source replaces a fluorescent light source	No
EPREL ID	522918,2176383,2366013
Model number	AC32689,AC70573,AC84508

# Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### DOWNLOAD DATA

Documents and certificates	Document name	
Declarations of conformity	LED PAR M2 lamp	
Declarations of conformity	LED PAR20 PAR38 E27	
Declarations of conformity	LED lamp PAR	
Declarations of conformity UKCA	LED PAR20 PAR38 E27	
Declarations of conformity UKCA	LED lamp PAR	
Photometric and lighting design files	Document name	
Spectral power distribution	Everlight 67-23ST HKE 2700K	
	Declarations of conformity  Declarations of conformity  Declarations of conformity  Declarations of conformity UKCA  Declarations of conformity UKCA  Photometric and lighting design files	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854071195	Folding box	100 mm x 100 mm x 149 mm	208.00 g	1.49 dm³
4099854071201	Shipping box	312 mm x 211 mm x 163 mm	1440.00 g	10.73 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For dimming conformity see www.ledvance.com/dim
- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.osram-lamps.com/guarantee

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.