

PRODUCT DATASHEET LED Classic A 50 Filament Mirror P 6.5W 827 Silver E27

LED CLASSIC A MIRROR P | LED lamps, classic bulb shape with mirror bulb crown



Areas of application

- Perfect for decorative installations
- Mirror lighting
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Long lifetime of up to 15,000 h
- Lower energy consumption than incandescent or halogen lamps
- Easy relamping thanks to compact design
- Instant 100 % light, no warm-up time
- Lamps with innovative LED "filament" technology

Product features

- Bulb crown coating: silver
- Lamp made of glass
- Good quality of light; color rendering index Ra; ≥ 80; constant chromaticity



827 Silver E27



TECHNICAL DATA

Electrical data

| Nominal wattage | 6.5 W |
|--|----------|
| Construction wattage | 6.50 W |
| Nominal voltage | 220240 V |
| Operating mode | AC Mains |
| Claimed equiv. conventional lamp power | 50 W |
| Nominal current | 38 mA |
| Type of current | AC |
| Inrush current | 0.1 A |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Max. lamp number on MCB B10 A | 789 |
| Max. lamp number on MCB B16 A | 1263 |
| Total harmonic distortion | 90 % |
| Power factor λ | > 0.50 |

Photometrical data

| Luminous flux | 650 lm |
|---|------------|
| Luminous efficacy | 100 lm/W |
| Lumen main.fact.at end of nom.life time | 0.93 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | 80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcm |
| Rated LLMF at 6,000 h | 0.80 |
| Flickering metric (Pst LM) | ≤1.0 |
| Stroboscope effect metric (SVM) | ≤0.4 |




EPREL data spectral diagram PROF LEDr 2700K

Light technical data

| Beam angle | 300 ° |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight



| Overall length | 105.00 mm |
|------------------|-----------|
| Diameter | 60.00 mm |
| Maximum diameter | 60 mm |
| Product weight | 31.00 g |

Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|--------------------------------------|-----------|
| Maximum temperature at tc test point | 70 °C |

Lifespan

| Lifespan L70/B50 at 25 °C | 15000 h |
|--|---------|
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service lifetime | 0.93 |
| Rated lamp survival factor at 6,000 h | ≥ 0.90 |

Additional product data

| Base (standard designation) | E27 |
|-----------------------------|--|
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| | Dimmable | No |
|--|----------|----|
|--|----------|----|

Certificates & Standards

| Energy efficiency class | F 1) |
|--|----------------|
| Energy consumption | 7.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / UKCA |
| Photobiological safety group acc. to EN62778 | RG0 |

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference

| LOGISTICAL DATA | |
|---|-----------|
| Temperature range at storage | -20+80 °C |
| Energy labelling regulation data acc EU 2019/2015 | |

LEDCLA50MIR S 6

| Lighting technology used | LED |
|---|------|
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | E27 |

| Connected light source (CLS) | No |
|--|-----------------|
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Standby power | 0 W |
| Networked standby power for CLS | not applicable |
| Claim of equivalent power | Yes |
| Length | 105.00 mm |
| Height | 60.00 mm |
| Width | 60.00 mm |
| Chromaticity coordinate x | 0.463 |
| Chromaticity coordinate y | 0.42 |
| R9 Colour rendering index | 1 |
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.90 |
| Displacement factor | ≥0.5 |
| LED light source replaces a fluorescent light source | No |
| EPREL ID | 1361348 |
| Model number | AC45210,AC45210 |

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|----------------------------|---------------|
| POF | Declarations of conformity | LED CLASSIC |

| Photometric and lighting design files | Document name |
|---------------------------------------|--------------------------|
| IES file (IES) | LED CLA50 MIR S 2700 E27 |

827 Silver E27

| Photometric and lighting design files | Document name |
|---------------------------------------|---|
| LDT file (Eulumdat) | LED CLA50 MIR S 2700 E27 |
| Spectral power distribution | EPREL data spectral diagram PROF LEDr 2700K |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854062742 | Folding box | 60 mm x 60 mm x 111 mm | 45.00 g | 0.40 dm ³ |
| 4099854062759 | Shipping box 10 | 315 mm x 131 mm x 126 mm | 544.00 g | 5.20 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.