

## PRODUCT DATASHEET LS/PD MULTI3 CI

LS/PD MULTI 3 CI (NEW) | Light and presence sensor, recessed ceiling, moveable



---

### Areas of application

- Offices
- Corridors
- Classrooms
- Training rooms
- Stairways
- Sanitary areas

---

### Product benefits

- Particularly small construction

---

### Product features

- Ceiling installation sensor with moveable sensor head
- Connection via four-pole screw terminal or modular 4c4p-connector

---

## TECHNICAL DATA

### Electrical data

|                 |      |
|-----------------|------|
| Mains frequency | 0 Hz |
|-----------------|------|

### Dimensions & Weight

|                |          |
|----------------|----------|
| Length         | 50.00 mm |
| Width          | 50.00 mm |
| Height         | 25.00 mm |
| Diameter       | 50,0 mm  |
| Product weight | 30.00 g  |

### Colors & materials

|               |       |
|---------------|-------|
| Product color | White |
|---------------|-------|

### Temperatures & operating conditions

|                           |            |
|---------------------------|------------|
| Ambient temperature range | 0...+50 °C |
|---------------------------|------------|

### Capabilities

|                               |                                             |
|-------------------------------|---------------------------------------------|
| Dimmable                      | No                                          |
| Maximum installation height   | 4 m                                         |
| Detection area                | 6 m <sup>1)</sup>                           |
| Detection angle               | 80 ° <sup>2)</sup>                          |
| Type of installation          | On-top ceiling mounting/Ceiling integration |
| Operating range, light sensor | 20...600 lx <sup>3)</sup>                   |

1) Maximum diameter

2) Approximately

3) Approximately, measured at the sensor

### Certificates & Standards

|                           |      |
|---------------------------|------|
| Approval marks – approval | CE   |
| Protection class          | III  |
| Type of protection        | IP20 |

---

## EQUIPMENT / ACCESSORIES

- Surface mounting in connection with SENSOR KIT
- Suitable for MULTleco, DIM MULTleco, DALI MULTleco control unit
- Suitable for DALI Professional Sensor Coupler

---

## DOWNLOAD DATA


| Documents and certificates                                                       |                                        | Document name                                                                |
|----------------------------------------------------------------------------------|----------------------------------------|------------------------------------------------------------------------------|
|  | User instruction / safety instructions | 334180_LS/PD MULTI 3 CI – light and presence sensor for ceiling installation |
|  | Declarations of conformity             | 334067_LMS MULTI3 SENSORS                                                    |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4008321916648 | Folding box<br>1             | 170 mm x 34 mm x 91 mm               | 93.00 g      | 0.53 dm <sup>3</sup> |
| 4008321916655 | Shipping box<br>10           | 245 mm x 188 mm x 204 mm             | 961.40 g     | 9.40 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## ADDITIONAL CATALOG INFORMATION



|   |      |      |      |      |      |
|---|------|------|------|------|------|
| h | 20 m | 25 m | 30 m | 40 m | 50 m |
| A | 25 m | 33 m | 40 m | 50 m | -    |
| B | 45 m | 53 m | 60 m | 70 m | 70 m |

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.