


TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W
Nominal voltage	220...240 V
Nominal current	200 mA
Type of current	DC
Inrush current	5.13 A
Suitable for DC input	Yes
Input voltage DC	198...264 V
Operating frequency	0/50/60 Hz
Mains frequency	0/50/60 Hz
Total harmonic distortion	5 % ¹⁾
Power factor λ	> 0.95 ¹⁾
Surge capability (L-N)	1 kV

¹⁾ Full load at 230 V/50 Hz

Dimensions & Weight



Product weight	98.00 g
----------------	---------

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	85 °C

Lifespan

Number of switching cycles	60000
----------------------------	-------

Additional product data

Mercury content	0.0 mg
-----------------	--------

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Type of protection	IP20
Standards	Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 62384

Country-specific categorizations

Order reference	DR DALI-P-30/22
-----------------	-----------------


LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Length	105.00 mm
Height	25.00 mm
Width	45.00 mm





Accessories Optional


Product image	Product name	EAN
	DR AY DALI-P CLAMP DUO	4099854400605

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Disconnect mains before installation.
- Do not open enclosure-housing.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	DR DALI P
 Legal information	Informationstext 18 Abs 4 ElektroG
 Legal information	Safety Insert G11205865
 Declarations of conformity	DR_AY DALI-P_CLAMP DUO

Documents and certificates		Document name
	Declarations of conformity UKCA	DR AY_DALI-P_CLAMP DUO

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075845367	Folding box 1	52 mm x 112 mm x 34 mm	108.00 g	0.20 dm ³
4058075845374	Shipping box 20	305 mm x 265 mm x 130 mm	2460.00 g	10.51 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.