

PRODUCT DATASHEET

TR SP ZOOM DIM P 20W 93040 WT

TRACKLIGHT SPOT ZOOM DIM CCT | Dimmable 3-phase tracklight spot with mechanical zoom lense and CCT switch



Areas of application

- Direct replacement for luminaires using HID lamps
- Accent lighting
- Galleries, museums
- Shops, changing rooms, shop windows
- Hotels, restaurants

Product benefits

- Dimmable 3-phase tracklight spot with mechanical zoom lense
- No distraction from the illuminated objects thanks to the reduced design
- Low flicker light thanks to special electronic control gear

Product features

- Multi Color function: 3000 K and 4000 K
- Mechanical zoom lens with a beam angle of 21° to 50°
- Dimmable (3% - 100%) via potentiometer directly on each luminaire
- Color rendering index CRI 90
- Initial color consistency: ≤ 3 SDCM
- Rotation angle: 350°, tilt angle: 90°
- Durable die-cast aluminum housing
- Available in matt white (like RAL9003), matt black (like RAL9005)
- Luminaire efficacy: up to 120 lm/W



TECHNICAL DATA

Electrical data


Nominal wattage	20.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	500.000 mA
Inrush current	0.56 A
Inrush current time T_{h50}	49 μ s
Max. number of luminaires per miniature circuit breaker B16	140
Max. number of luminaires per miniature circuit breaker C10	87
Max. number of luminaires per miniature circuit breaker C16	140
Power factor λ	> 0.90
Total harmonic distortion	< 15 %
Protection class	I
Surge capability (L-N)	1000 V
Surge capability (L/N-Ground)	2000 V
Operating mode	Integrated LED driver

Photometrical data


Luminous flux	1600 lm / 1300 lm ¹⁾
Luminous efficacy	80 lm/W / 65 lm/W ²⁾
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool white
Color rendering index Ra	> 90
Standard deviation of color matching	≤ 3 sdc _m
Luminous intensity	1650 cd
Low flicker	Yes
Flickering metric (Pst LM)	< 1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	21 °...50 °
UGR	< 23

1) 1600lm@50°, 1300lm@21°


2) 80lm/W@50°, 65lm/W@21°




TR SP ZOOM DIM P 20W 93040
WT 3000K 21D




TR SP ZOOM DIM P 20W 93040
WT 3000K 50D




TR SP ZOOM DIM P 20W 93040
WT 4000K 21D




TR SP ZOOM DIM P 20W 93040
WT 4000K 50D




TR SP ZOOM DIM P 20W 93040
WT 3000K 21D



TR SP ZOOM DIM P 20W 93040
WT 3000K 50D




TR SP ZOOM DIM P 20W 93040
WT 4000K 21D



TR SP ZOOM DIM P 20W 93040
WT 4000K 50D

Dimensions & Weight

Diameter	72.00 mm
Length	189.00 mm
Height	256.00 mm
Product weight	720.00 g



TR SP ZOOM DIM P

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9003
Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Adapter, 3-phase
Type of protection	IP20/IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	1-10V
Mounting type	Surface
Mounting location	Mounting track
Application environment	Indoor
Adjustable	Yes
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Lifespan L80/B10 at 25 °C	35000 h ¹⁾
Lifespan L80/B50 at 25 °C	45000 h
Lifespan L90/B10 at 25 °C	25000 h
Number of switching cycles	25000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	500 mA
ECG - Output ripple current	< 3 %

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Standards	CE / ENEC / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from September 2025
Added function	MULTI SELECT

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	G11247141 TRACKLIGHT SPOT ZOOM DIM CCT
	Legal information	Safety Insert G11218810
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	LSI G11254551 TRACKLIGHT SPOT ZOOM DIM CCT
	Declarations of conformity	TRACKLIGHT SPOT

Documents and certificates		Document name
	Declarations of conformity UKCA	TRACKLIGHT SPOT
	Certificates	ENEC TR SP ZOOM
Photometric and lighting design files		Document name
	IES file (IES)	TR SP ZOOM DIM P 20W 93040 WT 3000K 21D
	IES file (IES)	TR SP ZOOM DIM P 20W 93040 WT 3000K 50D
	IES file (IES)	TR SP ZOOM DIM P 20W 93040 WT 4000K 21D
	IES file (IES)	TR SP ZOOM DIM P 20W 93040 WT 4000K 50D
	LDT file (Eulumdat)	TR SP ZOOM DIM P 20W 93040 WT 3000K 21D
	LDT file (Eulumdat)	TR SP ZOOM DIM P 20W 93040 WT 3000K 50D
	LDT file (Eulumdat)	TR SP ZOOM DIM P 20W 93040 WT 4000K 21D
	LDT file (Eulumdat)	TR SP ZOOM DIM P 20W 93040 WT 4000K 50D
	UGR file (UGR table)	TR SP ZOOM DIM P 20W 93040 WT 3000K 21D
	UGR file (UGR table)	TR SP ZOOM DIM P 20W 93040 WT 3000K 50D
	UGR file (UGR table)	TR SP ZOOM DIM P 20W 93040 WT 4000K 21D
	UGR file (UGR table)	TR SP ZOOM DIM P 20W 93040 WT 4000K 50D
	Light distribution curve type cone	TR SP ZOOM DIM P 20W 93040 WT 3000K 21D
	Light distribution curve type cone	TR SP ZOOM DIM P 20W 93040 WT 3000K 50D
	Light distribution curve type cone	TR SP ZOOM DIM P 20W 93040 WT 4000K 21D
	Light distribution curve type cone	TR SP ZOOM DIM P 20W 93040 WT 4000K 50D
	Light distribution curve type polar	TR SP ZOOM DIM P 20W 93040 WT 3000K 21D
	Light distribution curve type polar	TR SP ZOOM DIM P 20W 93040 WT 3000K 50D
	Light distribution curve type polar	TR SP ZOOM DIM P 20W 93040 WT 4000K 21D


Photometric and lighting design files		Document name
	Light distribution curve type polar	TR SP ZOOM DIM P 20W 93040 WT 4000K 50D
CAD/BIM files		Document name
	BIM Revit 3D	Tracklight Spot Zoom Dim
	CAD STEP 3D	TL ZOOM DIM 20W 93040.
Tender texts		Document name
	Tender documents	TRACKLIGHT SPOT ZOOM DIM CCT 20W 93040 WT-en


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854616181	Folding box 1	211 mm x 247 mm x 100 mm	881.00 g	5.21 dm³
4099854616198	Shipping box 4	440 mm x 267 mm x 230 mm	4060.00 g	27.02 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION





References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.