

# PRODUCT DATASHEET P CLAS A 60 9 W/2700 K E27

PARATHOM® CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

## **Product benefits**

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design

#### Product features

- Professional LED lamps for line voltage
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Long lifetime up to 25,000 h
- Good quality of light; color rendering index  $\rm R_{a}\!\!: \geq 80;$  constant chromaticity





# TECHNICAL DATA

# Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	52 mA
Type of current	AC
Inrush current	4 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	65
Max. lamp number on MCB B16 A	76
Power factor λ	> 0.70

## Photometrical data

Luminous flux	806 lm
Nominal useful luminous flux 90°	806 lm
Luminous efficacy	89 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

# Light technical data

Beam angle	220 °
Warm-up time (60 %)	< 1.00 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	110.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm

Product weight	33.00 g
Troduct weight	50.00 g
Temperatures & operating conditions	
Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	100 °C
Lifespan	
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value / LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)
Capabilities	
Dimmable	Yes
Certificates & Standards	
Energy efficiency class	F 1)
Energy consumption	9.00 kWh/1000h
Type of protection	IP20
Standards	CE / ROHS / ERP
Photobiological safety group acc. to EN62778 RG1	
Dountry-specific categorizations	E (lowest efficiency)
Order reference	LEDPCLA60D 9W/8

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Correlated colour temperature type	SINGLE_VALUE
Length	110.00 mm
Height	60.00 mm
Width	60.00 mm
EPREL ID	1403221
Model number	AC24705

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075462571	Folding box	61 mm x 61 mm x 109 mm	47.00 g	0.41 dm <sup>3</sup>
4058075462588	Shipping box 10	318 mm x 133 mm x 124 mm	592.00 g	5.24 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For dimming conformity see www.ledvance.com/dim
- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.