

PRODUCT DATASHEET

P CLAS B 40 4 W/2700 K E27

PARATHOM® Retrofit CLASSIC B | LED lamps, classic mini-candle shape

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Lower energy consumption than incandescent or halogen lamps

Product features

- Professional LED lamps for line voltage
- Beam angle: up to 300°
- Not dimmable
- Base: E14
- Lifetime: up to 15,000 h
- Lamp made of glass
- Good quality of light; color rendering index $R_a \geq 80$; constant chromaticity

403 Forbidden

TECHNICAL DATA

Electrical data

| | |
|--|-------------|
| Nominal wattage | 4 W |
| Construction wattage | 4.00 W |
| Nominal voltage | 220...240 V |
| Claimed equiv. conventional lamp power | 40 W |
| Nominal current | 32 mA |
| Type of current | AC |
| Inrush current | 1.5 A |
| Operating frequency | 50...60 Hz |
| Mains frequency | 50...60 Hz |
| Max. lamp number on MCB B10 A | 400 |
| Max. lamp number on MCB B16 A | 480 |
| Power factor λ | > 0.50 |

Photometrical data

| | |
|---|------------|
| Luminous flux | 470 lm |
| Nominal useful luminous flux 90° | 470 lm |
| Luminous efficacy | 117 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | 80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcn |
| Rated LLMF at 6,000 h | 0.80 |
| Flickering metric (Pst LM) | 1.0 |
| Stroboscope effect metric (SVM) | 0.9 |

EPREL data spectral diagram PROF
LEDr 2700K

Light technical data

403 Forbidden

| | |
|---------------------|----------|
| Beam angle | 300 ° |
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight

| | |
|------------------|----------|
| Overall length | 92.00 mm |
| Diameter | 35.00 mm |
| Maximum diameter | 35 mm |
| Product weight | 20.00 g |

Temperatures & operating conditions

| | |
|--------------------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Maximum temperature at tc test point | 65 °C |

Lifespan

| | |
|--|---------|
| Lifespan L70/B50 at 25 °C | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service lifetime | 0.70 |
| Rated lamp survival factor at 6,000 h | ≥ 0.90 |

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | E27 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |

| | |
|----------------|--|
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value / LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance) |
|----------------|--|

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

| | |
|-------------------------|------|
| Energy efficiency class | E 1) |
|-------------------------|------|

403 Forbidden

| | |
|--|----------------|
| Energy consumption | 4.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / EAC |
| Photobiological safety group acc. to EN62778 | RG0 |

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | LEDPCLB40 4W/82 |
|-----------------|-----------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|--|--------------|
| Lighting technology used | LED |
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | E27 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | Yes |
| Length | 92.00 mm |
| Height | 35.00 mm |
| Width | 35.00 mm |
| Chromaticity coordinate x | 0.463 |
| Chromaticity coordinate y | 0.420 |
| R9 Colour rendering index | >0 |
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.90 |
| Displacement factor | 0.40 |
| LED light source replaces a fluorescent light source | No |
| EPREL ID | 523190 |
| Model number | AC32379 |


Safety advice


- Do not touch the lamp if broken.

403 Forbidden

– Must not be used if outer bulb is defective.

DOWNLOAD DATA

| Documents and certificates | Document name |
|---|---------------------|
|  Declarations of conformity | LED lamps CLA,B,G,P |

| Photometric and lighting design files | Document name |
|--|---|
|  Spectral power distribution | EPREL data spectral diagram PROF LEDr 2700K |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075591479 | Folding box 1 | 39 mm x 39 mm x 109 mm | 34.00 g | 0.17 dm ³ |
| 4058075591486 | Shipping box 10 | 205 mm x 87 mm x 123 mm | 389.00 g | 2.19 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

403 Forbidden