PRODUCT DATASHEET HCI-TT 70 W/830 SUPER 4Y

POWERBALL HCI®-TT SUPER 4Y | Metal halide lamps with ceramic technology for enclosed luminaires



Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Exhibition halls and trade fairs
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- Up to 15 % higher lumen maintenance factor compared to HCI-TT standard lamps
- Up to 30 % higher lum. efficacy for lamps ≤ 100 W (comp. to NAV-T Super 4Y/6Y)
- Good color rendering
- Operation in existing HPS installations as ignition voltage of IEC 60662 is met
- Energy savings of up to 70 % when replacing mercury vapor lamps (HQL)
- Optimum energy efficiency on POWERTRONIC® PTo 3DIM ECGs
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

Product features

- White light due to POWERBALL® ceramic technology
- Light color: warm white (830 WDL)
- Extended service lifetime: 4 years (at approx. 11 h/day)





- Very high luminous efficacy: up to 125 lm/W
- Lamp survival factor: 95 % after 16,000 h burning time
- Average lifetime: up to 24,000 h
- ErP compliant according to EU Regulation 245/2009
- Dimmable on conventional control gears and electronic control gears

TECHNICAL DATA


Electrical data

Nominal wattage	70 W	
Construction wattage	75.00 W	
Nominal voltage	95 V 1.8/5.0 kVp ¹⁾	
Ignition voltage		
Operating mode	Conventional control gear (CCG) and ignitor, Electronic control gear (ECG)	
Nominal current	1000 mA	
PFC capacitor at 50 Hz	12 μF	

¹⁾ Minimum / Maximum

Photometrical data

Luminous flux	8000 lm
Luminous efficacy	107 lm/W
Color temperature	3200 K
Color rendering index Ra	80
Light color	832
Rated LLMF at 2,000 h	0.92
Rated LLMF at 4,000 h	0.90
Rated LLMF at 6,000 h	0.89
Rated LLMF at 8,000 h	0.88
Rated LLMF at 12,000 h	0.85
Rated LLMF at 16,000 h	0.83
Rated LLMF at 20,000 h	0.75
Rated lamp efficacy (standard co.)	104 lm/W
UV protection	Yes



502820_HCI_TT_ET_830_SUPER_4Y

Dimensions & Weight

Overall length	150.00 mm
Light center length (LCL)	102,0 mm
Diameter	35.00 mm
Product weight	50.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	350 °C
Maximum permitted base edge temperature	210 °C

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.98
Rated lamp survival factor at 8,000 h	0.97
Rated lamp survival factor at 12,000 h	0.97
Rated lamp survival factor at 16,000	0.95
Rated lamp survival factor at 20,000 h	0.78
Lifespan B10	18000 h
Lifespan B5	16000 h
Lifespan B50	24000 h
Operation mode LLMF/LSF	50 Hz

Additional product data

Base (standard designation)	E27
Mercury content	8.0 mg
Mercury-free	No
Design / version	Clear
System guarantee level	3 (2/5)

Capabilities

	Dimmable	Yes 1)
Ī	Burning position	Any
	Enclosed luminaire required	Yes

¹⁾ In combination with POWERTRONIC PTo

Certificates & Standards

Energy efficiency class	F
Energy consumption	84.70 kWh/1000h

Country-specific categorizations

ILCOS	MT/UB-70/830-H/E/SL-E27-32/155
Order reference	HCI-TT 70W/830

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	MH
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	156.00 mm
Height	35.00 mm
Width	35.00 mm
Chromaticity coordinate x	0.420
Chromaticity coordinate y	0.394
Beam angle correspondence	SPHERE_360
EPREL ID	1535148
Model number	AC01721

Safety advice

- Where possible, use a timer igniter (switch-off time of at least 15 minutes). Otherwise, switch off the luminaire for at least 15 minutes if a brief interruption has occurred to the mains voltage supply.
- Disconnect mains before installation.
- Must not be used if outer bulb is defective.
- Do not stare at the operating light source: The luminaire should be positioned so that prolonged staring into the luminaire at a distance closer that 4 m is not expected.
- Lamp to be used only in a closed luminaire.

DOWNLOAD DATA

	Documents and certificates Document name		
POF	Declarations of conformity	Discharge lamps excluding fluorescent lamps	
	Photometric and lighting design files	Document name	
	Spectral power distribution 502820_HCI_TT_ET_830_SUPER_4Y		

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899378339	Sleeve 1	39 mm x 39 mm x 196 mm	76.00 g	0.30 dm ³
4052899378346	Shipping box 12	168 mm x 130 mm x 212 mm	953.00 g	4.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For more information on the system guarantee and the terms and conditions of the guarantee visit www.ledvance.com/system-guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.