

PRODUCT DATASHEET ST 151 LONGLIFE

Starters for series operation at 230 V AC (ST 151, ST 172) | Starters for series operation at 230 V AC

Product features

- Temperature range for reliable cut-out: -20...+80 °C



July 20, 2025, 15:24:30 ST 151 LONGLIFE

TECHNICAL DATA

Electrical data

Nominal wattage	22.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Dimensions & Weight

Diameter	21,5 mm
Product weight	6.43 g

Additional product data

Product remark Starters are available in two different designs, with identical technical features	Mercury content	0.0 mg	
	Product remark	-	

Capabilities

Dimmable	No

Country-specific categorizations

Order reference	ST 151 LONGLIFE

Energy labelling regulation data acc EU 2019/2015

Length	40.30 mm
Height	21,5 mm
Width	21.50 mm

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	Glow starter for fluorescent lamps	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300854083	Unpacked 1	37 mm x 19 mm x 20 mm	6.64 g	0.01 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300012803	Unpacked 1	36 mm x 18 mm x 21 mm	12.60 g	0.01 dm ³
4050300797885	Tray 25	111 mm x 59 mm x 111 mm	169.46 g	0.73 dm ³
4050300797892	Shipping box 400	227 mm x 179 mm x 227 mm	2796.25 g	9.22 dm ³
4050300212876	Shipping box 1,200	400 mm x 235 mm x 325 mm	8362.00 g	30.55 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.